

Tubos para intercambiadores. Principales medidas BWG. *ASTM Heat exchanger tube - principal BWG sizes*

Outside Diameter		BWG					
		20	18	16	14	12	10
		Wall thickness mm					
		0.89	1.24	1.65	2.11	2.77	3.40
inches	mm	Weight per kg/m (average wall)					
¾	9.53	0.193	0.257				
½	12.7	0.263	0.356	0.457			
5/8	15.88	0.334	0.455	0.588			
¾	19.05	0.405	0.553	0.729	0.895		
7/8	22.22	0.46	0.64	0.837	1.046		
1	25.4	0.546	0.75	0.981	1.234	1.574	
1¼	31.75	0.688	0.947	1.244	1.574	2.014	
1½	38.1	0.832	1.144	1.514	1.904	2.454	
1 3/4	44.5		1.342	1.774	2.244	2.894	3.5
2	50.8		1.549	2.034	2.574	3.334	4.03
2½	63.5		1.949	2.554	3.244	4.214	5.13
3	76.2		2.345	3.084	3.914	5.094	6.19
3½	88.9		2.729	3.609	4.584	5.974	7.27
4	101.6			4.134	5.254	6.854	8.35
4 1/2	114.3			4.654	5.924	7.734	9.43